



Cem-FIL® Fibres

For Glass fibre Reinforced Concrete (GRC)

PRODUCT DESCRIPTION

Cem-FIL® Alkali Resistant Glassfibres were first developed by the Building Research Establishment in the UK more since 1970, and were later manufactured under license in Japan and the USA. They have the longest service history, and have been used in more than 80 countries worldwide to create some of the world's most stunning architecture.

Following the development of Cem-FIL® fibres we also partnered the development of:

- Equipment and processes used in the manufacture of GRC
- Advanced matrix development
- Design and performance guidelines
- Application development

As a part of the Owens Corning Composite Solution Business (the world leader in glass fibre reinforcements) we have developed a wide range of Cem-FIL® products to satisfy the needs of the developing markets and the diverse processes used.

We have amassed a wealth of experience both in the manufacture of Cem-FIL® fibres, and GRC products, which we use to jointly develop the industry with our customers.

PRODUCT APPLICATION

Cem-FIL® GRC products can be produced by one of many manufacturing processes. The most common are the spray and vibration-cast premix, but products may also be spun, filament-wound, laminated on a moving conveyor, pressed, vacuum-formed, extruded, etc.

As the manufacturing processes have evolved, so have the fibres. A large range of fibres has been developed to satisfy the needs of the markets, and to provide optimum processing efficiency and performance in the chosen manufacturing methods.

In addition to the manufacturing processes, guidelines and techniques for moulding, achieving different surface finishes, and enhanced mechanical properties have also been developed.

Our plan is always to enhance the usability, desirability and understanding of GRC, so that GRC products can satisfy the needs of an ever-expanding market.

IMPORTANT CHARACTERISTICS

Cem-FIL® FIBRES:

- > 37 years in-service use worldwide
- Proven durability and performance
- Comprehensive product range
- Excellent processing characteristics
- High tensile strength and elastic modulus
- Manufactured under ISO 9001 approved Quality Management System

GRC:

- Lightweight and thin section
- Strong and durable
- Excellent mouldability
- Attractive and versatile

Cem-FIL® FIBRES: Typical Properties

Strand Tensile Strength	1.7	GPa
Elastic Modulus	72	GPa
Specific Gravity	2.68	gr/m ³
Strain to Failure	2.4	%
Softening Point	860	°C
Fire Performance	Incombustible	



CEM-FIL® PRODUCTS

The following represents only part of the Cem-FIL® standard product range: For enquiries about products not shown, please contact our representatives.

Assembled Roving

Product Code:	Roving Tex	Strand Tex	Filament Ø (µm)	No. of Strands
61/2	2500	83	14	32



Typical Applications:

61/2 – a dual-purpose roving most widely used for all spray-up applications, but can also be used as a chopping roving (chopped by the customer and used to produce vibration-cast premix GRC)

Chopped Strands

Type:	Product Code:	Strand Tex	Filament Ø (µm)	Lengths (mm)	
High Integrity:	- High Tex	63/1	135	18	6, 12, 18
	- Medium Tex	60/3	82	14	6, 12, 18
	- Low Tex	62/3	45	14	6, 12
Water Dispersible	- Low Humidity	70/30	n/a	20	3, 6, 9, 12
	- High Humidity	W-70	n/a	14	6, 12



Typical Applications:

- 63/1 – general vibration-cast premix applications
- 60/3 – general vibration cast or sprayed premix applications
- 62/3 – vibration cast or sprayed premix applications requiring greater reinforcing effect at low fibre addition rates
- 70/30 – reinforcement of architectural face-mixes of GRC products
- W-70 – reinforcement of calcium silicate products, and replacement of asbestos fibres



CHARACTERISTICS OF GRC

Thin and Light-Weight

- Rapid erection without heavy lifting equipment
- Reduced load gives savings to foundation and structure costs
- Economical transport

Durable

- GRC will not rot or corrode, and resists biological attack
- No embedded steel, so no spalling or staining
- Advanced matrices can be used to further enhance long-term ductility, reduce shrinkage, etc. Examples: GRC Cement, Asahi Super Suncrete, Cem-Star Metakaolin

High Quality Matrix

- Low permeability and a hard dense surface
- Carbonation 1/10th the rate of concrete
- High compressive and flexural strength
- Low maintenance

Attractive and Versatile


- Can be formed with complex shapes, colours and textures
- Can be used to accurately simulate natural materials (timber, rock, stone, etc)
- Making aesthetic solutions possible

Non-Combustible

Excellent Acoustic Performance

TYPICAL PROCESSES AND APPLICATIONS

Spray-Up	<ul style="list-style-type: none"> Architectural façade cladding Permanent formwork Acoustic barriers and parapets Artificial rock Field irrigation channels
Vibration-cast Premix	<ul style="list-style-type: none"> Architectural mouldings Drainage channels Telecom housings Simulated roof slates Promenade tiles Open Access Floors
Premix Spray	<ul style="list-style-type: none"> Renovation components Street / garden furniture Mouldings
Centrifugal casting	<ul style="list-style-type: none"> Pipes
Filament Winding	<ul style="list-style-type: none"> Telecommunication masts Foundry crucibles Sewer re-lining panels
Automated / Robotic Spray	<ul style="list-style-type: none"> Architectural façade cladding Sewer re-lining panels Permanent formwork
Continuous Lamination	<ul style="list-style-type: none"> Canal bank protection Corrugated sheet Low-cost housing



Cem-FIL[®] Fibres

For Glass fibre Reinforced Concrete (GRC)

FINISHES

GRC may be painted, stained, or may be produced with tiles, granite or other stone veneer finishes.

To achieve integral coloured finishes, Cem-FIL[®] GRC can use white cement and pigments. Textures can be achieved either from the mould, or by acid etching or sand-blasting to expose the texture and colour of the sand or aggregate.

ADDITIONAL CHARACTERISTICS OF CEM-FIL[®] GRC

Typical Mechanical Properties of Cem-FIL [®] GRC at 28 days					
Property:		Unit	Simultaneous Spray	Premix Spray	Vibration-Cast Premix
Fibre Content		Weight %	5	2.5 – 4.2	3
Bending Strength	MOR	MPa	22 – 32	12 - 14	10 – 12
	LOP	MPa	7 – 13	7 – 10	6 – 9
Tensile Strength	UTS	MPa	8 – 12	5 – 9	4 – 7
	BOP	MPa	5 – 7	4 – 6	4 – 6
Compressive Strength		MPa	50 - 80	40 - 60	40 – 60
Shear Strength	Inter-laminar	MPa	3 - 5	N/A	N/A
	In-Plane	MPa	8 – 12	4 – 7	4 – 7
Impact Strength		kJ/m ²	10 – 25	10 – 15	10 – 15
Elastic Modulus		GPa	10 – 20	10 – 20	10 – 20
Strain to Failure		%	0.6 – 1.2	0.2 – 0.3	0.1 – 0.2
Dry Density		t/m ³	1.9 – 2.1	1.8 – 2.0	1.8 – 2.0

Europe

Holger ZORN
TEL: +32.2.674.8318
FAX: +32.2.662.0815
Cem-fil@owenscorning.com

Middle East & Africa

Brian MARTEN
EFAX: +44 (0) 8701123811
Cem-fil@owenscorning.com

North America

James PATTERSON
TEL: +1 623-566-0260
FAX: +1 208-730-4581
Cem-fil@owenscorning.com

Asia Pacific

Peter RIDD
TEL: +44 1275.390.968
FAX: +44 117.370.1075
Cem-fil@owenscorning.com



OWENS CORNING
COMPOSITE MATERIALS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO 43659
1.800.GET.PINK™
www.owenscorning.com
www.ocvreinforcements.com

EUROPEAN OWENS CORNING
FIBERGLAS, SPRL.
166, CHAUSSÉE DE LA HULPE
B-1170 BRUSSELS
BELGIUM
+32.2.674.82.11

OWENS CORNING – OCV ASIA PACIFIC
SHANGHAI REGIONAL HEADQUARTERS.
2F OLIVE LVO. MANSION
620 HUA SHAN ROAD
SHANGHAI 200040
CHINA
86.21.62489922

This information and data contained herein is offered solely as a guide in the selection of a reinforcement. The information contained in this publication is based on actual laboratory data and field test experience. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application to determine its suitability before committing to production. It is important for the user to determine the properties of its own commercial compounds when using this or any other reinforcement. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe any patent or violate any law safety code or insurance regulation.

Pub. No. 10010974. Owens Corning reserves the right to modify this document without prior notice. © 2009 Owens Corning

Cemfil_GRC_Application_ww_04-2009_Rev0