



INNOVATIONS FOR LIVING™

# Cem-FIL®



## PRODUCT SELECTION GUIDE

GRC

The easy way to find the Cem-FIL® solution

Application	Cem-FIL® 62 45, 82 tex 6, 12, 18 mm	Cem-FIL® 60 45, 82, 135 tex 6, 12, 18 mm	Cem-FIL® 61 roving (82) 2500	Cem-FIL® 54 roving (76) 2450	Cem-FIL® 5325 direct roving 320 - 2400 tex	Cem-MAT 120 gr/m2
Premix	•	•	•			
Spray			•	•		
Industrial			•	•		•
Filament winding					•	

## Performance benefits guide

Product benefits	Cem-FIL® 62 45, 82 tex 6, 12, 18 mm	Cem-FIL® 60 45, 82, 135 tex 6, 12, 18 mm	Cem-FIL® 61 roving (82) 2500	Cem-FIL® 54 roving (76) 2450	Cem-FIL® 5325 direct roving 320 - 2400 tex	Cem-MAT 120 gr/m2
Fibers dispersion	••	•••	••			
Workability	•	•••	•			
Abrasion resistance during mixing	•	••	•			
Reduced water demand		••				
High performance with low dosage	••	•				
Adaptation to complicated profiles	•••	•••	••	•••		•
Reproduction of detail	•••	•••	••	•••		
Unwinding			••	••	••	•••
Easy chopping			•••	••		••
Split efficiency			•••	••		
Mechanical performance	•••	••	•••	•••	••	••

- Good
- Very good
- Excellent